

Leistungstabellen | performance tables | tableaux de performance | tabelle delle prestazioni

LSP/E		150				200				330				500			
Glattrohrwärmetauscher Heating coil Échangeurs de chaleur Serpentino	m ²	1.0				1.6				2.0				2.6			
Vorlauf Supply Alimentation Mandata	°C ΔT = 10°C	50	60	70	80	50	60	70	80	50	60	70	80	50	60	70	80
Spitzenleistung Top performance Sortie crête Potenza di picco	45°C l/10 min.	70	80	95	105	95	115	135	160	145	170	200	224	210	245	275	310
	45°C l/h	183	260	340	415	280	405	530	650	375	530	690	845	510	710	915	1120
Dauerleistung Continuous output Régime permanent Potenza continua	45°C l/h	138	216	295	370	220	345	470	595	275	430	590	745	360	560	765	970
Leistung Performance Performance Prestazione	kW (10°C – 45°C)	5.6	8.8	12.0	15.2	9.0	14.1	19.2	24.3	11.2	17.6	24.0	30.4	14.6	22.9	31.2	39.5
Spitzenleistung Top performance Sortie crête Potenza di picco	60°C l/10 min.	-	-	70	80	-	-	105	120	-	-	155	175	-	-	220	245
	60°C l/h	-	-	210	265	-	-	325	410	-	-	430	540	-	-	580	720
Dauerleistung Continuous output Régime permanent Potenza continua	60°C l/h	-	-	165	220	-	-	265	350	-	-	330	440	-	-	430	570
Leistung Performance Performance Prestazione	kW (10°C – 60°C)	-	-	9.6	12.8	-	-	15.4	20.5	-	-	19.2	25.6	-	-	25.0	33.3
Heizwasser Primär Heating water primary Eau de chauffage primaire Riscaldamento acqua primaria	m ³ / h	-	-	-	1.3	-	-	-	2.1	-	-	-	2.6	-	-	-	3.4
Druckverlust Pressure loss Perte de charge Perdita di pressione	mbar	-	-	-	20	-	-	-	70	-	-	-	150	-	-	-	310

LSP/C		150				200				330				500			
Glattrohrwärmetauscher Heating coil Échangeurs de chaleur Serpentino		1.0				1.6				2.0				2.6			
Vorlauf Supply Alimentation Mandata		50	60	70	80	50	60	70	80	50	60	70	80	50	60	70	80
Spitzenleistung Top performance Sortie crête Potenza di picco	45°C l/10 min.	75	90	110	125	110	135	160	190	160	195	230	260	230	270	320	360
	45°C l/h	225	330	430	535	350	515	680	840	460	665	875	1080	620	890	1155	1425
Dauerleistung Continuous output Régime permanent Potenza continua		180	285	385	490	290	455	620	780	360	565	775	980	470	740	1005	1275
Leistung Performance Performance Prestazione		7.4	11.6	15.8	20.0	11.8	18.5	25.2	31.9	14.7	23.1	31.5	39.9	19.1	30.0	40.9	51.9
Spitzenleistung Top performance Sortie crête Potenza di picco	60°C l/10 min.	-	-	80	90	-	-	115	135	-	-	170	195	-	-	245	275
	60°C l/h	-	-	260	330	-	-	405	520	-	-	530	675	-	-	715	900
Dauerleistung Continuous output Régime permanent Potenza continua		-	-	215	285	-	-	345	460	-	-	430	575	-	-	565	750
Leistung Performance Performance Prestazione		-	-	12.6	16.8	-	-	20.2	26.9	-	-	25.2	33.6	-	-	32.8	43.7
Heizwasser Primär Heating water primary Eau de chauffage primaire Riscaldamento acqua primaria		-	-	-	1.7	-	-	-	2.8	-	-	-	3.4	-	-	-	4.5
Druckverlust Pressure loss Perte de charge Perdita di pressione		-	-	-	30	-	-	-	120	-	-	-	200	-	-	-	420